



**Converge
Engineering**

8855 Washington Blvd. Suite 4
Roseville, CA 95678
916-636-7917 Info@convergeengineering.com

Solid State Drive Shredders



CE-3150SD
CE-3200SD



CE-275SD
CE-2100SD



CE-HM2
CE-HM4
CE-HM6

Features:

- Choice of shred width 2mm, 4mm, 6mm, 3/8"
- Viewing window & hour meter
- Choice of paint color
- UL certified controls

Requirements:

- 120V is only available with CE-115SD
- CE-130SD and larger requires 3 phase power

Options:

- Dust collection
- Fork pockets
- Mobile truck installation
- Gaylord dust cover with access panel

THROUGHPUTS:

Model #	HP	Cutters	SSD / Hr
CE-HM2	2 + 3	3/8" to 2mm	50
CE-HM4	2 + 3	3/8" to 4mm	75
CE-HM6	2 + 3	3/8" to 6mm	100
Model #	HP	Cutters	SSD / Hr
CE-115SD	1.5	3/8"	200
CE-130SD	3.5	3/8"	600
CE-275SD	7.5	3/8"	1800
CE-2100SD	10	3/8"	2000
CE-3200SD	20	3/8"	2400

TECHNICAL DATA:

	CE-HM2 CE-HM4 CE-HM6	CE-115SD CE-130SD	CE-275SD CE-2100SD	CE-3200SD
Infeed Slot	8.5"W x 1.5"H	5" W x 2" H	11"W x 2.5"H	20"W x 4"H
Output	2 Cft Bin	17" L x 11" W x 12" H Bin	53"H Conveyor	53"H Conveyor
Voltage	208/230/460V	120/208/230/460V	208/230/460V	208/230/460V
Dimensions	61"L x 58"W x 71"H	45" L x 21" W x 44" H	77"L x 56"W x 56"H	94"L x 75"W x 67"H
Weight	3000 - 4000 Lbs.	1100 Lbs.	2700 - 3400 Lbs.	4700 - 5100 Lbs.